

### Date Generated: 25.12.24

# **T10 Product Data Sheet**

#### **Material Details**

Grade:	T10. (Type: Paper & Fabric - SRBP & SRBF (Not manufactured by The Attwater Group))
Description:	Phenolic Cotton. Electrical Grade (Not manufactured by The Attwater Group)
Comments:	A high quality Phenolic cotton tube manufactured from fine weave cloth and phenolic resin. T10 tube exhibits excellent electrical and mechanical properties and may be machined to a fine finish.
Specifications:	BSEN61212 PFCC21 (Which supersedes BS6128 PFCC81). The closest NEMA equivalent to this specification is LE.
Body Colour:	Light brown
Standard Finish:	Ground (unless otherwise stated)
Size:	1220mm trimmed (max) Thickness Range: Min ID 8.0mm, Min wall 1.0mm(Ground) 2.0mm(as produced). †

## **General Properties**

Property	Unit of measure	Typical Value
Density	g/cm3	1.35
Water Absorption	mg	2.5

¥ Where relevant, the flammability test method is used solely to control and monitor consistency of production. Under no conditions should the results be considered in relation to fire hazards under actual conditions of use.

### **Electrical Properties**

Property	Unit of measure	Typical Value
IR (24hrs Water Immersed)	G 🛛	0.09
IR (Dry)	G 🛛	0.09
Radial Electric Strength	MV/m	3.5

## **Mechanical Properties**

Property	Unit of measure	Typical Value
Cohesion	-	180
Axial Compressive	-	200

# **Thermal Properties**

Property	Unit of measure	Typical Value	
Thermal Rating Continuous	°C	120	

#### **Notes**

• Datasheet Issue No. 1

Disclaimer: The above values are based upon routine test data and do not form the basis of a supply contract. These products may be used in a diverse range of applications and whilst every effort is made to ensure the information in this data sheet is accurate, it must be stressed that it is the user's responsibility to ensure suitability for the intended end use.

Source: https://www.attwater.com/products/t10s/